

**NIKKOR** Z

24 - 50 mm f / 4 - 6.3

BE BOLD. BE FREE.

Meet the super-portable NIKKOR Z 24-50mm f/4-6.3. Expansive landscapes and scene-setting interiors. Captivating portraits and candid street shots. There's not much you can't capture with a zoom lens this versatile. And nowhere you can't go with a zoom lens this small.

FEATURES

PORTABLE FULL-FRAME ZOOM

This mirrorless lens is the smallest, lightest full-frame zoom around.¹ Covers a versatile 24–50 mm wide-angle to standard focal length range and allows use of 52 mm filters.

RETRACTABLE DESIGN

The button-free retractable-lens mechanism is quick and easy to use. Simply extend or retract the lens by rotating the zoom ring.

NIKON Z IMAGE QUALITY

The Z mount's impressive light-gathering capability ensures photos and movies are beautifully sharp and evenly illuminated throughout the frame.

RICH COLOUR

ED glass and aspherical lens elements minimise distortion throughout the zoom range for sharper images with deep contrast and vivid colour.

SHARP FOCUS ON CLOSE-UP DETAILS

A minimum focus distance of just 0.35 m throughout the zoom range puts you in control of the frame, from close-up to infinity.

GREAT FOR MOVIES

Shoot 4K video footage with natural, wide perspectives. Focusing is quiet and focus breathing when shooting movies is reduced for professional-looking results.

SMOOTH, SILENT AUTOFOCUS

Thanks to the additional light gathered by the Z mount and an ultra-quiet stepping motor, focusing is fast, silent, and accurate.

CUSTOMIZABLE CONTROL RING

Offers quick, silent access to key camera settings. Use it for aperture control, exposure compensation, or ISO adjustments.

¹ Shortest length and lightest weight among standard zoom lenses for full-frame interchangeable-lens mirrorless cameras released as of 21st July 2020

INCLUDED ACCESSORIES



FRONT LENS CAP LC-52B



REAR LENS CAP LF-N1

OPTIONAL ACCESSORIES



LENS CASE CL-C4



LENS HOOD HB-98



NIKKOR Z 24-50mm f/4-6.3

CAPTURE TOMORROW



TECHNICAL SPECIFICATIONS NIKKOR Z 24-50 mm f/4-6.3

Type	Nikon Z mount
Format	FX/35mm
Focal length	24–50 mm
Maximum aperture	f/ 4 to 6.3
Minimum aperture	f/ 22 to 36
Lens construction	11 elements in 10 groups (including 2 ED elements and 3 aspherical elements)
Angle of view	FX format: 84° to 47° DX format: 61° to 31° 30'
Focal length scale	Graduated in millimeters (24, 28, 35, 40, 50)
Focusing system	Internal focusing system
Minimum focus distance	0.35 m 1.15 ft) from focal plane at all zoom positions
Maximum reproduction ratio	0.17 × (50 mm zoom position)
No. of diaphragm blades	7 (rounded diaphragm opening)
Aperture range	24 mm zoom position: f/4 to 22 50 mm zoom position: f/6.3 to 36
Filter-attachment size	52 mm (P = 0.75 mm)
Dimensions	Approx. 73.5 mm (2.9 in.) maximum diameter x 51 mm (2.1 in.) (distance from camera lens mount flange when lens is retracted)
Weight	Approx. 195 g (6.9 oz)
Autofocus	Yes
Internal focusing	Yes
Focusing	Auto, Manual
Supplied accessories	Lens Cap LC-52B (front cap), Lens Cap LF-N1 (rear cap)
EAN code	4960759904256
Material code	JMA712DA

Nikon reserves the right to change the appearance, specifications, and performance of this product at any time and without prior notice. July 2020



CAPTURE TOMORROW

NIKKOR Z
24 - 50 mm f / 4 - 6.3

24-50 mm STANDARD ZOOM | FX MIRRORLESS | SILENT AF | RETRACTABLE | PORTABLE



Camera body: Z 5 © Shohki Eno